

EX90

Multimedia Projector



Ultra bright
and reliable.

Features/Benefits

- Ultra bright 2600 lumens — perfect for use in any lighting
- Full-time color, no color breakup, no rainbows — 3LCD, 3-chip optical engine
- Razor-sharp quality, HD-compatible — native XGA resolution
- Extra flexibility — included carrying case and VGA-to-component video adapter
- Outstanding support — two-year limited warranty, next-business-day Road Service
- Energy efficient — long-life E-TORL™ lamp and low power consumption projector
- Simple setup — 1.2x optical zoom and auto keystone correction
- Convenient control — Instant On, Instant Off® and A/V Mute



Ordering Information

| Product Name | Product Code | UPC |
|----------------------------------|-------------------|------------------------|
| EX90 Multimedia Projector | V11H307220 | 0 10343 86865 6 |
| Replacement lamp | V13H010L42 | 0 10343 86411 5 |
| Replacement air filter | V13H134A13 | 0 10343 86412 2 |

EX90 Multimedia Projector Specifications

Projection System

High aperture Epson 3LCD technology

Projection Method

Front/rear/ceiling mount

LCD

Driving Method

Epson Poly-silicon TFT Active Matrix

Pixel Number

786,432 dots (1024 x 768) x 3 LCDs

Native Resolution

XGA

Aspect Ratio

4:3 (supports 16:9)

Pixel Arrangement

Cross stripe

Projection Lens

F-number

1.6 – 1.74

Focal Length

18.4 – 22.12 mm

Zoom Ratio

Optical zoom 1.0 – 1.2

Lamp

E-TORL

E-TORL 170 W UHE

Life*

3000 hours (High Brightness Mode)

4000 hours (Low Brightness Mode)

Screen

Width Ratio (distance/width)

1.40 – 1.68 (4:3 aspect ratio)

Size (projected distance)

30" – 300" (2.7' – 34.2')

Keystone Correction

Automatic, 0 – 11 degrees vertical

Manual, ±30 degrees vertical

Brightness (High Brightness Mode)

Up to 2600 lumens (ISO 21118 Standard)

Contrast Ratio (High Brightness, Game Mode)

Up to 400:1

Brightness Uniformity (typical)

90%

Color Reproduction

16.77 million full-time colors

Dimensions (W x D x H)/Weight

Including Feet

12.9" x 9.6" x 4.3"

Excluding Feet

12.9" x 9.6" x 3.6"

Weight

6.0 lb/2.7 kg

Effective Scanning Frequency Range

Pixel Clock

13.5 MHz – 162 MHz

Horizontal

15 KHz – 92 KHz

Vertical

50 Hz – 85 Hz

Remote Control

Features

Source search, power, aspect, color mode, volume, e-zoom, A/V mute, freeze, menu, page up and down, help, auto

Display Performance

Native

1024 x 768

Resize

640 x 480

800 x 600

1280 x 1024

1400 x 1050

1600 x 1200

Video I/O

Display Performance

NTSC: 560 line

PAL: 560 line

(depends on observation of the multi-burst pattern)

Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/

SECAM

480i, 480p, HDTV: 720p, 1080i

Interfaces

Computer/Component video: Mini D-sub HD 15 pin

S-video: Mini DIN

Composite video: RCA

Composite audio RCA x 2

Monitor out

USB Type B (mouse and keyboard control)

Operating Angle (Remote)

Right/left ± 30 degrees

Upper/lower ± 15 degrees

Operating Distance

19.7 ft (6 m)

Other Features

Audio Output

1 W monaural

Audio Signal Input

500m Vrms/47K ohm

Operating Temperature

41 ° to 95 °F (5 ° to 35 °C)

Power Supply Voltage

100 – 240 V ±10%, 50/60 Hz AC

Power Consumption

248 W, 4.1 W standby (network off)

Fan Noise

35 dB (High Brightness Mode)

28 dB (Low Brightness Mode)

Security

Kensington®-style lock provision, anchor (metal) bar for security lock or cable, user logo protection function, password protection

Support — The Epson ConnectionSM

Pre-sales Support

U.S. and Canada

800-463-7766

Internet Web Site

www.epson.com

Projector resources available at

presentersonline.com

Service Programs

Two-year limited warranty, 90-day lamp warranty, Epson Road Service Program and Epson PrivateLine[®] dedicated toll-free support (U.S. and Canada only)

Contents

VGA to component adapter, computer cable, projector remote control, batteries, soft carrying case, CD-ROM, Quick Setup Sheet, PrivateLine support card, password protection sticker

Accessory Part Numbers

| | |
|--|------------|
| Replacement remote | 1456639 |
| Universal projector ceiling mount | ELPMBPJF |
| Advanced projector ceiling mount with precision gear | ELPMBPRG |
| High security projector ceiling mount | ELPMBATA |
| Adjustable suspended ceiling channel kit | ELPMBP01 |
| False ceiling plate kit | ELPMBP02 |
| Structural round ceiling plate | ELPMBP03 |
| Adjustable extension column (pipe) 6" – 9" | ELPMBPC01 |
| Security flex foot kit | ELPMBF01 |
| Kensington security lock | ELPSL01 |
| Distribution amplifier | ELPDA01 |
| Component-to-VGA video adapter | ELPKC19 |
| Component-to-VGA video cable | ELPSV01 |
| S-video cable | ELPKS63 |
| Swiss Gear backpack | V12H001K60 |
| Simple Soft carrying case | ELPKS62 |
| Wheeled soft case | ELPKS61 |
| Soft shoulder case for projector and laptop | ELPKS58 |
| ATA molded hardshell case | ELPKS61 |
| 50" portable screen | ELPSC06 |
| 60" portable pop-up screen | ELPSC0 |
| 80" portable pop-up screen | ELPSC08 |
| 83.6" classroom style pull-down screen | ELPSC09 |
| Duet™ screen by Accolade | ELPSC80 |
| Image Presentation Camera (ELPDC05) | V12H162020 |

* Lamp life results will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Packaging Specifications

EX90 Multimedia Projector

Dimensions 16.8" x 14.9" x 7.2" (W x D x H)

Weight 11.7 lb

Replacement Lamp

Dimensions 6.3" x 5.5" x 5.6" (W x D x H)

Weight 0.7 lb

Master Carton

Dimensions 28.4" x 13.1" x 6.8" (W x D x H)

Weight 9.1 lb

Units Per Master Carton 10

Replacement Air Filter

Dimensions 3.9" x 1.2" x 4.9" (W x D x H)

Weight 0.88 lb

Master Carton

Dimensions 12.8" x 5.3" x 4.7" (W x D x H)

Weight 1.1 lb

Units Per Master Carton 10



Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.
3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. Epson and Instant Off are registered trademarks and Epson Exceed Your Vision and E-TORL are trademarks of Seiko Epson Corporation. PowerLite and PrivateLine are registered trademarks, Duet and Accolade are trademarks, and Epson Connection and Epson PresentersOnline are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2008 Epson America, Inc. CPD-25268 3/08